

SUPER BRAKE WASHER BCE-300

America's original brake washer pays for itself in months by eliminating the need for rental brake washers and aerosol cleaners.

COMPLYS WITH OSHA ASBESTOS REGULATION 29 CFR 1910.1001

OSHA-preferred, low pressure brake washing system eliminates exposure to airborne brake dust during drum removal and brake cleaning.

Air Regulator

Limits air pressure to 32 PSI (2.2 bar); eliminates the need to adjust or otherwise regulate shop air pressure.

ECONOMICAL

Clean all four brakes on 30 cars for less than the cost of one can of aerosol brake cleaner.

Construction

Broad-based dolly keeps the unit stable.
Steel-reinforced undercarriage makes it very strong.
Large industrial-strength casters make for easy movement throughout the shop.
Polyethylene plastic will not rust, chip or dent.
Welded construction stands up to the daily rigors and rough handling common to vehicle repair facilities.

Cover

Cover stored on dolly (shown left of drum in right photo).
Cover doubles as a catch-basin when servicing vehicles on safety stands.

CareFree Disposal System™

Solid waste: As simple as throwing out the trash. Wastewater: Follow operating instructions and just pour it down the drain. Disposal Guidebook included with each machine.



National Stock Number

NSN 4940-01-396-0573

575 Prospect Street, Unit 213 • Lakewood, NJ 08701-5040 USA

CLAYTON

+1 (800) 248-8650

+1 (732) 363-2100

Fax +1 (732) 364-6084

www.jclayton.com

BCE-300

SealTite™ Primary Microfilter

This 15 micron efficiency filter extends the useful life of the cleaning solution. A molded, self-sealing collar fits securely into the basin to prevent particles from bypassing the filter. For best results, this disposable filter is changed monthly or approximately every 150 vehicles.

Basin:

21" X 16" X 4 1/4" (53 cm. x 41 cm. x 11 cm.) basin provides ample room to loosen, remove and clean car and light truck drums.

Splash-Gard™ Pad

This fiber pad keeps liquid running off the brakes from splashing on the floor. It also serves as a prefilter to remove coarse particles from the solution and prevent small brake parts from becoming lost in the Primary Microfilter.

Grille

Vinyl-clad grille supports the brake drum and parts during cleaning and protects the Splash-Gard™ pad.

T-N-T Plus™ Concentrated Cleaner

T-N-T™ Plus is non-toxic, non-flammable, biodegradable and derived from natural sources. One liter of concentrate makes 10 gallons (38 L) of potent cleaning solution. Each machine comes with a liter of T-N-T™ Plus concentrate, one Primary Microfilter and one Splash-Gard™ pad.

Flow-Thru Brush

New parts cleaning brush features stiff, durable bristles for extended life and vigorous cleaning action.



Injector Nozzle

Flexible wand to flush the drum before removing the it. Suppressing the dust before removal prevents exposure to hazardous even if a hammer is needed to free the drum.

Air Powered Pump

Eliminates the risk of electrical shock. After removing the tires, the technician connects the air supply hose to the washer to begin cleaning.

Basic Starter Kit PN 300-102

Recommended for purchase with a new machine, this kit consists of 8 Primary Microfilters, 8 disposal bags and 2 liters of T-N-T™ Plus.

Basic Supply Kit PN 300-152

Recommended for purchase after the first year of use, this kit contains approximately one year's usage of supplies: 9 Primary Microfilters, 9 disposal bags, 3 liters of T-N-T™ Plus, one brush tip and one Splash-Gard™ pad.

575 Prospect Street, Unit 213 • Lakewood, NJ 08701-5040 USA

CLAYTON

sales@jclayton.com

+1 (732) 363-2100

FAX +1 (732) 364-6084

www.jclayton.com