

ATTENTION: \_\_\_\_\_ FAX: \_\_\_\_\_



*Preserving The Earth's Natural Resources — Assuring A Safe Workplace For All*

## BRAKE WASHER PUMP WARRANTY INSTRUCTIONS

The pump and regulator are warranted for one year from the date of original sale (if the washer was purchased from a Clayton distributor, please contact your distributor for warranty replacement). In order to receive warranty service on Brake Washer pumps, **both the pump and regulator must be returned** to Clayton Associates for inspection.

First, remove all input and output tubes from the pump. The tubes are all attached to the pump with quick-disconnects. Alongside each port on the pump is a small plastic tab. Sliding this tab away from the port will release the fitting, and the hose can be removed with a gentle tug. Next, unscrew the pump from the basin. It is held in place by two screws which are visible just above the pump.



To remove the regulator, first unbolt the regulator assembly from the basin. It is held to the basin with two bolts. Once the assembly is freed from the basin, remove the hoses from the regulator by unthreading the fittings from the regulator body. The regulator can then be removed from its metal bracket by removing the black plastic nut which holds the regulator to the bracket.

Fill out the information below, then place both items into a small box with this form, and return them to Clayton Associates, Inc. at the address below. No warranty replacements will be issued before both the pump and regulator have been received. After we have reviewed the warranty claim, we will immediately send out new parts. Customer is responsible for shipping costs associated with returning items for warranty. Clayton Associates will cover the cost of shipping the warranty replacements out.

**Ship parts to: Clayton Associates RGA, 1650 Oak Street, Lakewood, NJ 08701**

Company Name: _____
Point of Contact: _____
Phone Number: _____
Return Address: _____
_____
_____